

## HP DesignJet T950 36-in Printer

Active 2Y9H1A Series →

### Specifications

#### All Specs

Additional storage	2.7 GB reprint queue
Color(s) of printing supplies	Cyan, magenta, yellow, matte black
Connectivity, standard	Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n
Electromagnetic compatibility	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (RED Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Korea (KCC)
Energy star certified	Yes
Environmental certification	ENERGY STAR, EPEAT, UL ECOLOGO® certified inks, CE marking (including WEEE, RoHS, REACH, ErP). In compliance with applicable WW RoHS materials restriction requirements.
Finished output handling	Sheet feed, roll feed, front-loading input tray (100 sheet capacity), sheet organizer (50 sheet capacity[4]), stacker (40 sheet capacity[4]), automatic horizontal cutter
Functions	Print
HP ePrint capability	Yes
Ink drop	6 pl (C, M, Y); 12.6 pl (mK)
Ink types	Pigment-based (C, M, Y, mK)
Internal Storage	None
Line accuracy	±0.1%[2]
Manufacturer Warranty	Two-year limited hardware warranty. Warranty and support options vary by product, country and local legal requirements.
Maximum optical density (black)	15 L* min/1.7 D[3]
Media sizes standard (metric rolls)	369 to 914 mm
Media sizes supported	Input tray: A4, A3; Manual feed: A4, A3, A2, A1, A0
Media sizes, custom	Front-loading input tray: 210 x 279 to 305 x 457 mm; Manual feed: 210 x 279 to 914 x 1676 mm
Media thickness	Up to 11.8 mil
Media thickness (metric)	Up to 0.3 mm
Media types	Bond and coated paper (bond, coated, heavyweight coated, plain, bright white, blueprint), technical paper (natural tracing), film (clear, matte), photographic paper (ID satin, ID gloss), self-adhesive (adhesive matte/gloss, adhesive polypropylene gloss), Polypropylene (matte)
Media weight, recommended	60 to 280 g/m <sup>2</sup> (roll/manual feed); 64 to 220 g/m <sup>2</sup> (front-loading input tray)
Media width, maximum	914 mm
Memory	1 GB
Model size	914 mm

Network ready	Standard
Non-Operating Humidity Range	0 to 95% RH
Non-printable area (cut-sheet)	5 x 5 x 5 x 5 mm
Non-printable area (roll media)	5 x 5 x 5 x 5 mm
Number of print cartridges	4 (C, M, Y, mK)
Operating altitude	Up to 3000 m
Operating humidity range	20 to 80% RH
Operating temperature range	41 to 104°F
Orderable supplies	HP Original Ink: HP 738 cartridges (Black, Cyan, Magenta, Yellow), and HP 739 printhead
Post consumer recycled plastic in hardware by weight of plastic	40%
Power	Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max
Power consumption	35 W (printing), <5.5 W (ready), <2.5 W (sleep), <0.2 W (standby). Auto-scheduled printer on/off usage.
Print cartridge volume delivered	300 ml, 130 ml
Print head nozzles	1376 per color; 5504 in total
Print heads	1 (C, M, Y, mK)
Print languages	TIFF, JPEG, URF, PDF, HP-GL/2, HP-RTL, CALS G4
Print multi-size files in one click	Yes
Print quality color (best)	Up to 2400 x 1200 optimized dpi
Print speed	21 sec/page on A1, 120 A1 prints per hour[1]
Print Technology	Ink
Print technology	HP Thermal Inkjet
Printer drivers included	Raster driver for macOS and Windows, HP Click Driver for Windows 11, HP-GL/2 driver for Windows
Printing path	Wi-Fi Direct, remote printing, HP Click App, HP Click Driver for Windows 11, Apple AirPrint and HP app for Android and iOS devices, Windows and macOS printer drivers, printing support for Chrome OS
Product display name	HP DesignJet T950 Large Format 36-in Plotter Printer with Automatic A1/D and A3/B Printing in One Device, Compact Size
Recommended media	HP Universal Bond Paper (FSC® certified)[5] (recyclable)[6]; HP Coated Paper (FSC® certified)[5] (recyclable)[6]; HP Heavyweight Coated Paper (FSC® certified)[5] (recyclable)[6]
Registration required	No
Remote print enabled	Yes
Roll external diameter	140 mm
Roll maximum input	1
Roll maximum weight	13 kg
Safety	USA and Canada (CSA certified); EU (RED Directive, EN 62368-1 compliant); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)

Security features	HP Secure Boot, whitelisting, Security event logging, Disable network ports and protocols, SNMPv3, 802.1x compatibility, TLS/SSL, Semi-permanent-queue Erase, HP Web JetAdmin, HP Security Manager, SIEM Integration
Software included	HP Click App, HP Click Driver for Windows 11, HP app for Windows, macOS, Android, and iOS
Storage	2.7 GB reprint queue
Storage temperature range	-13 to 131°F
Supported Primary Applications	Line drawings; Renderings; Presentations; Maps; Posters
Technical features	A3 input tray;Stacker;A3 sheet organizer;Auto-power on/off scheduler;Max. resolution 2400 x 2400 dpi;HP Wolf Pro Security;130/300 ml cartridges;HP Flex Tech Inks
Theoretical minimum line width	0.02 mm (via raster driver)
UNSPSC code	43212104
What's in the box	HP DesignJet T950 Printer, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord

## Logistics

Minimum dimensions (W x D x H)	1407 x 720 x 967 mm
Package dimensions (W x D x H)	1575 x 630 x 780 mm
Package weight	84 kg
UNSPSC code	43212104
UPC number	(AB1) 198701770640; (ABG) 196548313099; (ACJ) 196548313105; (B19) 196548313112; (B1K) 196548313129; (BCD) 196548313136
Weight	56 kg
What's in the box	HP DesignJet T950 Printer, printhead, introductory ink cartridges, printer stand, spindle, guide, warranty flyer, power cord

## Specifications

[1] Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.

[2]  $\pm 0.1\%$  of the specified vector length or  $\pm 0.2$  mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.

[3] With HP Universal Instant Dry Photo Gloss media with Original HP inks.

[4] Based on test results using 80 g/m<sup>2</sup> plain paper and standard configuration. Capacity is subject to paper type, printed file, and ambient conditions.

[5] BMG trademark license code FSC®-C115319, see <http://www.fsc.org>. HP trademark license code FSC®-C017543, see <http://www.fsc.org>

[6] Can be recycled through commonly available recycling programs.

## Legal disclaimer

Product image may differ from actual product

AirPrint; CE marking; ENERGY STAR; EPEAT green; IPv6 Ready; Mac; Wi-Fi Certified; Windows 11 Compatible