



Get blazing fast printing speeds, high-volume scanning, and easy management with LaserJet Pro.

This printer is built for maximum productivity with fast speeds and reliable hardware, delivering effortless everyday use from wherever work happens so you can focus more on your business.





Highlights

- Instant Ink for Laser available
- HP Smart app and Smart Adv/Pro
- HP Wolf Pro security
- · Automatic two-sided printing standard
- Fast print speed (40 ppm A4)
- High monthly duty cycle (80,000 pages)
- · 50 sheet ADF with single-pass, two-sided scanning

















Maximum productivity.

- Support your dynamic workteam with this high-speed smart printer, ideal for up to 10 users.
- Step up your workflow with HP Pro-class maximum print speed to meet high-demand environments.
- Scan both sides with a single pass. Dual-sided scanning allows your users to get more done in less time.
- Get productivity in the palm of your hand. Print, scan and get time-saving Shortcuts with HP Smart app. ²

Seamless management.

- Centralise print management for your enterprise. HP Web Jetadmin makes it easy with its suite
 of features. 4
- Set up your printers quickly wherever work happens. Cloud connectivity makes it easy for your IT team.
- Access your printers from a single dashboard. Smart Admin guides you through setup and gives IT visibility.³

HP Wolf Pro Security.

- Get printer security out of the box. Preconfigured settings mean it's ready when you are.
- Set up your printer security from the dashboard. Smart Admin makes IT configuration and monitoring easy. $^{\rm 3}$
- $\bullet \quad \text{Add a layer of security. PIN/pull option authenticates your print jobs only when you're present.}\\$
- Set configuration policies and validate settings universally with HP Security Manager.⁶

Hassle-free supplies management with Instant Ink.

- Enroll to save on Original HP Toner with Instant Ink. Get toner, delivery and recycling. ^{6,7,8}
- Never run out of toner with Instant Ink for laser.9
- With Instant Ink, get toner automatically delivered to workers or offices all on one consolidated bill.⁸
- With Instant Ink, you get to select the right plans for each of your printers. Change or cancel at any time.¹⁰

Product walkaround

- 1. Designed for workteams of up to 10 users
- 2. Pre-configured security settings
- 3. Walk-up USB
- 4. Automatic 2-sided printing
- 5. Hi-speed USB ports, built-in Gigabit Ethernet
- 6. Print speeds up to 40 ppm (A4), 350-sheet standard paper capacity



Accessories, Supplies and Support

Supplies	W1490A HP 149A Black Original LaserJet Toner Cartridge (Average cartridge yields 2,900 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
	W1490X HP 149X High Yield Black Original LaserJet Toner Cartridge (Average cartridge yields 9,500 standard pages. Declared yield value in accordance with ISO/IEC 19752.)
Accessories	D9P29A HP LaserJet Pro 550-sheet Feeder Tray
Service and Support	U42TZE - HP 3 year Next Business Day Service for LaserJet Pro MFP 410x U42U8PE - HP 1 year Post Warranty Next Business Day Service for LaserJet Pro MFP 410x

Technical specifications

Model	HP LaserJet Pro MFP 4102fdn Printer
Product number	27623F
Functions	Print, copy, scan, fax
Control panel	2.7" Color Touchscreen
Print	
Print technology	Laser Black (A4. normal): Up to 40 ppm : Black (A4. duplex): Up to 34 ipm
Print speed ¹	the state of the s
First page out ²	Black (M4, ready): As fast as 6.3 sec; Black (M4, sleep): As fast as 8.8 sec
Print resolution	Black (best): Fine Lines (1200 x 1200 dpi); Technology, HP FastRes 1200, HP ProRes1 200, Economode
Monthly duty cycle Printer smart software features ³	Up to 80,000 pages A4; Recommended monthly page volume: 750 to 4,000 Auto duplex and booklet printing, N-up printing, collation, watermarks, install printer driver only, Economode for toner savings, accepts a variety of paper sizes and types
Standard print languages	Autoropies and opposite printing, recept printing, containing, to a grant printing, containing, and a grant printing, and a grant printing, and a grant printing and a grant printin
Fonts and typefaces	ne ret. 6, ne ret. 6, p. p. possanju lever 3 embalion, ror, one, neave onite, rwo nasie: 84 scalable TrueType fons:
Print area	or statation more type norms Print margin Stop: 4.3 mm, Bottom: 4.3 mm, Left: 4.3 mm, Right: 4.3 mm; Maximum print area: 207.4 x 347.1 mm
Duplex printing	Finithinguis (p. 4.5 mir, buttuin. 4.5 mir, tert. 4.5 mir, regin. 4.5 mir, waxmun pinit area. 207.4 x 347.1 mir Automatic (default)
Copy	Automatic (delabit)
Copy speed	Black (A4): Up to 38 cpm
	ID Copy, Number of copies, Resize (including 2-Up); Lighter/Darker; Enhancements; Original Size; Binding Margin; Collation; Tray Selection; Two-Sided; Quality (Draft/Normal/Best); Save Current Settings; Restore Factory
Copier specifications	Defaults, Maximum number of copies: Up to 9999 copies; Reduce/Enlarge: 25 to 4009
Scan	
Scan speed ⁴	Normal (A4): Up to 29 ppm/46 ipm (b&w), up to 20 ppm/34 ipm (color) ;Duplex (A4): Up to 46 ipm (b&w), up to 34 ipm (color)
Scan file format	PDF, JPG, TIFF
Scanner specifications	Scanner type Flatbed, ADF; Scan technology: Contact Image Sensor (CIS); Scan input modes: Front-panel scan, copy, email, or file buttons; HP Scan software; and user application via TWAIN or WIA; Twain version: 2.3;
	Duplex ADF scanning: Ves; Scan size maximum (flatbed, ADF): 216 x 297 mm; Optical scan resolution: Up to 1200 x 1200 dpi
Scanner advanced features	Copy preview
Recommended monthly scan volume	750 to 4000
Scannable area	Maximum media size (flatbed): 216 x 297 mm; Minimum media size (ADF): 102 x 152 mm Maximum media size (ADF): 216 x 356 mm
Bit depth/ Grey scale levels	PRIAMIDITI THEOLOGICA (MALDEU), 216 x 297 mm; primini minimi media size (MDP), 102 x 152 mm praximum media size (MDP), 216 x 356 mm 24-bit / 256
Fax	ET 1817 E20
Fax	Yes, 33.6 kbps
Fax specifications	Fax memory. Up to 400 pages; Fax resolution: Standard: 203 x 98 dpi; Fine: Up to 203 x 196 dpi; Superfine: Up to 300 x 300 dpi; Quick dialing: Up to 200 numbers
	Auto fax reduction; Auto redailing, Delayed sending; Fax forwarding; TAM interface; Junk barrier; Distinction in quietection; Course page; Block fax; Save and load; Fax activity reports; Dial prefix setting. Print fax
Fax smart software features	Add for telegraphy determined between the control of the control o
Processor speed	1200 MHz
Connectivity	
Standard	1 Hi-Speed USB 2.0; 1 rear host USB; 1 Front USB port; Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE)
Mobile printing capability	HP Smart App; Apple AirPrint™; Mopria™ Certified
Supported nativary protocols	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint [™] , Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6
Supported network protocols	
Network capabilities	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint [™] , Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Gertificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No
Network capabilities Hard disk Memory	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint [™] , Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Network capabilities Hard disk Memory Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB
Network capabilities Hard disk Memory Media handling Number of paper trays	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3
Network capabilities Hard disk Memory Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;
Network capabilities Hard disk Memory Media handling Number of paper trays	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Ves, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (184 x 260 mm); 16K (18
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, PutoIP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB ;Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 73 mm); 16K (197 x 273 mm); 16K (198 x 270 mm); 16K (198 x
Network capabilities Hard disk Memory Media handling Number of paper trays Media size Media size Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard: Double Japan Postcard Rotated; Envelope #10; Envelope Monarch; Envelope B1; Envelope B1
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download No Standard: 512 MB; Maximum: 512 MB Standard: 512 MB; Maximum: 3 Paper (plain, ExcEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, preprinted, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 110.4 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (198 x 273 mm); Logstom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (210 x 340 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Officio (210 x 340 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Custom Size; A5-R; 4 x 6 in; B6 (JIS) ADR: Letter; Legal; A4; custom sizes 102 x 152 to 216 x 356 mm Standard input: 100-sheet tray 1, 250-sheet Automatic Document Feeder (ADF) Standard output: 150-sheet output bin Optional Input: Optional third 550-sheet tray ADF: Standard, 50 sheets Tray 1: 60 to 200 g/m²; tray 2, optional 550-sheet tray 3: 60 to 120 g/m²
Network capabilities Hard disk Memory Media handling Number of paper trays Media size Media size Media handling	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard: Double Japan Postcard Rotated; Envelope #10; Envelope Monarch; Envelope B1; Envelope D1; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 27
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 17.5 x 8 im; Statement; Tray 2.8 tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (19
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Gertificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4, A5, A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (197 x 273 mm); Lapanese Postcard; Double Japan Postcard Rotated; Envelope #S1; Envelope #S1; Envelope #S1; Envelope #S1; Envelope #S1; Envelope #S2; Envelope #S2; Envelope #S3; Envelope #S4; Envelope #S4; Envelope #S5; Envelop
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127t to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127t to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127t to 215.9 x 355.6 mm; Tray 2. 8 Tray 3: 727.3 mm; Lapanese Postcard; Double Japan Postcard Rotated; Envelope 815; Envelope 85;
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPVP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateleless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 175.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 175.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 7.7 x 1: 7.7 x 1.7
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL. Security and Certificate management; Management; SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Ves, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 125.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 76.2 x 127 to 125.9 x 355.6 mm; Tray 2.3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: 74.75. AG; 85 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (197 x 273 mm); Bapasee Postcard; Double Japan Postcard Rotated; Envelope Pate Stendepoe C5: Envelope C5:
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported fuertic): Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Lapasee Postcard; Double Japan Postcard Rotated; Envelope #B1, Envelope #B5; Envelope E5; Envelop
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels: Custom (metric): Tray 1: 76.2 x 127 to 215.5 x 35.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 35.5 mm Supported (metric): Tray 1: A4, A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Bapease Postcard; Double Japan Postcard Rotated; Envelope #BC; Envelope BC; Envelop
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SMMPv1, SMMPv2, SMMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels: Custom (metric): Tray 1: 76.2 x 127 to 215.5 x 35.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 35.5 mm Supported (metric): Tray 1: A4, A5; A6; B5 (JIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Bapease Postcard; Double Japan Postcard Rotated; Envelope #BC; Envelope BC; Envelop
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery: IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download No Standard: 912 MB, Maximum: 912 MB Standard: 912 MB, Maximum: 912 MB Standard: 912 MB, Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4: A5: A6; B5 (JIS): Oficio (216 x 240 mm); 16K (195 x 270
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media handling Media vipes Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple AirPrint™, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Sysiog, FTP PW Download Ves, via builti-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 512 MB; Maximum: 512 MB Standard: 512 MB; Maximum: 3 Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (netric): Tray 1: 762.x 127 to 215,9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (UIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (195 x 273 mm), Loustom Size, A5-R; 4 x 6 in; 5 f6 (UIS); Officio (216 x 340 mm); 16K (195 x 270 mm);
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media handling Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight	TCPIP IPVd, IPV6; Pint; TCPIP port 9100 Direct Mode, LPD (raw queue support only), Apple ArPrint**, Mopria, JPP Print; Discovery, SLP, Bonjour, Web Services Discovery; IP Config: IPVd (Bootp, DHCP, AutolP, Manual), IPV6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and certificate management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 512 MB Standard: 2; Maximum: 512 MB; Maximum: 512 MB Standard: 3; Maximum: 512 MB; Maximum: 512
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media handling Media vipes Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment	TCP/IP, IPv4, IPv6; Pint; TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Apple Arbrint* Morpia, IPP Print; Discovery SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootR, DHCPv6), SSL Security and Certificate management; Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via butil-in 10/100/1000Base-TX Ethernet; Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 512 MB; Maximum: 512 MB Standard: 512 MB; Maximum: 512 MB Standard: 2; Maximum: 512 MB Standard: 2; Maximum: 512 MB Standard: 2; Maximum: 512 MB Standard: 512 MB; Maximum: 512 MB; Maximum: 512 MB; Standard: 512 MB; Maximum:
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media size Media handling Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions	TCPIP_BN4_IN-SP: Print: TCP-IP_port 9100 Direct Mode. LPD Caw queue support only), Apple AirPrint*, Mopria, IPP Print: Discovery. SUR Bonjour, Web Services Discovery. IP Config. IPv4 (Boott), DHCP, AutolP, Manual), IPv6 (Sistates surface), Carl Acol and via Boutes, Stateful via OHO-Post), SSL Secrity and Certificate management. Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog. FTP FW Download Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: \$12 MB_Maximum: \$12 MB Standard: \$12 MB_Maximum: \$12 MB Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels; Custom (metric): Tray 1: 76.2 x 12 710 21.9 x 93.55 f.mm; Tray 2, 3: 104.9 x 148.9 s 10.21.5 y 3.55.5 mm Supported femoritic): Tray 1: A4, A5, A6; B5 (IIS); Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); pase postcard; bouble japan Postcard forbude; bagan Postcard forbude; Envelope Big. Envelope Big. Envelope Big. Envelope Cit. Custom Size; 4 x 6 in; 5 x 8 in; 5 s 8 in; 5 stenent; Tray 2; 5 sheets; 100; 5 (196 x 240 mm); 16K (195 x 270
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer weight Diperating environment Storage conditions Acoustics Power	TCPIE_PNG_PNG_PNG_PNG_TCP_Pp prf 9100 Direct Mode_LPD Caw queue support only), Apple AIPPINT_Mode_AIPPINT_MODE_AIPPINT_DISCOVERY_SUBJECT_PNG_BISCOVERY_PCORTER_ENVELOPE_ALTOR_Manual), IPV6 (Stateless Link-Local and via Boutes Statelet via Brocket Statelet Statelet Statelet Brocket Statelet Statelet Statelet Brocket Statelet Statelet Brocket Statelet Statelet Brocket Statelet Brocket Statelet Brocket Brocket Statelet Brocket Statelet Brocket Brocket Statelet Brocket Brocket Statelet Brocket Brock
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media handling Media size Media handling Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics	TCP/IE (PM4, IPM6, Print: TCP-IP port 9100 Direct Mode, IPD (raw queue support only), Apple AirPnirt*, Mogria, IPP Print; Discovery, SLP Bonjour, Web Services Discovery; IP Config IPM4 (Boot), OHCP, Autolip, Manual), IPV6 (Stateless Link-Local and via Routes, Statelut, was Indicated and via Routes, Statelut, and Certificate management, Management, SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Yes, via built-in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard 5.12 MB (Maximum: 512 MB) Sandard 2. Maximum: 512 MB Paper (plain, EcoFFFICIENT, Light, News), bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels: Custom (metric): Tray 1-76.2 x 1.27 to 21.5.9 x 355.6 mm; Tray 2, 3.104.9 x 148.59 to 21.5.9 x 355.6 mm Supported (metric): Tray 1-74.4 A5, A6, B6 (ISS), Otino (21.6 x 340 mm); IBK (193 x 270 mm); IBK (193 x
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer weight Diperating environment Storage conditions Acoustics Power	TCP/IE IPv4; IPv6; Print: TCP-IP port 9100 Direct Mode; LPD (raw queue support only), Apple AirPnint*, Mopria, IPP Print Discovery, SLP Boriquit, Web Services Discovery; IP Config IPv4 (Boott, DHCP, Autolit, Manual), IPv6 (Stateless Link-Local and via Routes; Satefull via McHove), SSL Security and Certificate management, Management; SNMPv1, SNMPv2, SNMPv3, HTTP/HTTP5, Syslog, FTP FW Download Ves, via bulti-in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X No Standard: 2 ; Maximum: 312 MB Maximum: 512 MB ; Maximum: 512 MB Standard: 2 ; Maximum: 312 MB Standard: 3 ; Maximum: 312 MB Standard: 2 ; Maximum: 312 MB Standard: 3 ; Maximum: 3 ; Maximu
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Number of paper trays Media types Media size Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer weight Diperating environment Storage conditions Acoustics Power	TCPIP (PM, EPK, Pinit, TCP) = port 91:00 Direct Mode, LPD (raw queue support only, Apple AirFinit)**. Morris, IPP Pinit, Discovery, IR Config III via (Bootf), DHCR, Autolif, Marual), IPv6 (Stateles, Linck, Card and via Notuce, Stateful via Horby-GS, SS. Security and certificate management: SNMPv1, SNMPv2, SNMPv2, HTTPHTTPS, Syslog, FTP FW Download Yes, via balt-in 10/100/1000083se-TX Ethernet, Gigabit, Auto-crossover Ethernet, Authentication via 802.1X No Standard: 512 MB, Maximum: 312 MB Standard: 2. Maximum: 312 MB, Maximum: 512 MB Standard: 2. Maximum: 312 MB, Standard: 3. Maximum: 512 MB Standard: 2. Maximum: 32 MB, Standard: 3. Maximum: 512 MB Standard: 3. Maximum: 512 MB, Standard: 3. Maximum: 512 MB Standard: 3. Maximum: 512 MB, Standard: 3. Maximum: 512 MB Standard: 3. Maximum: 512 MB, Standard: 5. Maximum: 512 MB, St
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	TCP/IP (PM, IPAC, Print TCP-IP) and 100 Direct Mode, LPD (raw queue support only, Apple AirPrint Mode, 1901). Southern Management: SNMP-V, SNM
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	TCV/PIP Piv4, IPV-E, Privat TCV-PiP port 9100 Direct Mode, LPD fraw quave support only, Apple AirPrivat*, Monagement; SNMPV1, SNMPV2, SNMPV3, HTTP/HTTPS, Syslog, FTP FW Download Yes, via built-in 10/100/100063ae-TX.Ethernet, Gigabit: Auto-crossover Ethernet; Authentication via 802.1 X No Standard: 512 MB, Maximum: 312 MB Standard: 512 MB, Maximum: 312 MB Standard: 2: Maximum: 312 MB Standard: 2: Maximum: 312 MB, Maximum: 512 MB Standard: 2: Maximum: 312 MB, Maximum: 512 MB Standard: 3: Maximum: 312 MB, Maximum: 512 MB,
Network capabilities Hard disk Memory Media handling Number of paper trays Media handling Media types Media handling Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications Sustainable impact specifications Country of origin	TCMP (Pivit, IPVS, Privit, TCPV) Pport 9100 Direct Mode, LPD frow quieue support only), Apple AirPrivin*, Mopris, LPD Privit, Discovery, SLR Banjaur, Web Services Discovery, IP Config pi M4 Blood? DHCR, AutoR, Manual, IPv6 (Stateless Linch Coad and via Nature Stateful via DHCPA). SSL Security and Certificate management. Management: SNAPV, SNAPV2, SNAPV2, SNAPV2, SNAPV3, HTTP/HTTPS, Syslog, FTP FW Download Nev. via built-in 10/100/100088se-TX Ethernet, Gigabit, Auto-crossover Ethernet; Authentication via 802.1 X No Standard: 512 M8 Maximum: 512 M8 Standard: 2, Maximum: 512 M8 Standard: 3, Maximum: 512 M8 Standard: 2, Maximum: 512 M8 Standard: 3, Maximum: 512 M8 Standard: 3, Maximum: 512 M8 Standard: 3, Maximum: 512 M8 Standard: 4, Maximum: 512 M8 Standard: 5, Maximum: 5, Maximu
Network capabilities Hard disk Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight Operating environment Storage conditions Acoustics Power Energy savings feature technology Certifications	TOT/IP Piv4, IPVS, Print: TOP-IP port 9100 Direct Mode, LPD fraw quave support only), Apple Air Print**, Morris, IPP Print; Discovery, SIR Banjaur, Will Services Discovery, IP Config Piv4 (Boott Piv4), Manual), IPV6 (Stateless Link-Coad and via Routes Stateful via DelPiv6), SSIS security and Certificate management. SNAPY1, SNAPV2, SNAPV2, SNAPV3, SNAPV2, SNAPV3, SNAPV2, SNAPV3, SNAPV2, SNAPV3, S

Footnotes

- 1 Measured using ISO/IEC 24734 and excludes first set of test documents. For more information, see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ² Requires' the HP Smart app download. For details on local printing requirements see www.hp.com/go/mobileprinting. Certain features/software are available in English language only, and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details at www.hpsmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. Fax capabilities are for sending a fax only. After 2 years, monthly fee applies to continue advanced features with HP Smart Advance. HP Smart Advance is not available in all countries. For more information, see www.hpsmart.com.
- ³ Easy setup and manage Requires use of Smart Admin Dashboard for printer setup and onboarding of users
- ⁴ HP Web Jetadmin is available for download at no additional charge at hp.com/go/webjetadmin.
- ⁵ HP JetAdvantage Security Manager must be purchased separately. To learn more, please visit hp.com/go/securitymanager.
- 6 Recycling: Program availability varies. Original HP cartridge return and recycling is currently available in more than 60 countries, territories and regions in Asia, Africa, Europe, and North and South America through the HP Planet Partners program, For details, see hp.com/recycle.
- Save up to 50% on toner (mono) Based on monthly subscription cost of HP Instant Ink monochrome toner service 1,500 page plan without purchase of additional sets of pages compared to cost per page to print ISO/IEC 24711 pages on most in-class, traditional A4 monochrome toner cartridge printers < 494 and MFPs priced < 672 using original standard-capacity integrated cartridges (toner and drum in one cartridge). Average CPP per country used to determine percent savings claim versus CPP for HP Instant Ink. Sale prices not considered for this study. Printers which only use XL cartridges excluded due to non-standard hardware & supplies model. Keypoint Intelligence September 2021 study commissioned by HP, based on publicly available information as of August 18, 2021. Printers selected by market share in IDC Quarterly Hardcopy Peripherals Tracker – Final Historical 2021Q2. For details: www.keypointintelligence.com/HPInstantInk.
- 8 Automatic delivery and consolidated bill: Printers require direct connection to the Internet for program participation. Internet access sold separately.

 9 Never run out: Based on plan usage, Internet connection to eligible HP printer, valid credit/debit card, email address, and delivery service in your geographic area.
- 10 Change or cancel: Change or cancel your plan at any time online. If you decide to cancel your HP Instant Ink you can go back to using HP original Standard or XL cartridges. Plan upgrades are effective immediately and the charges will be applied retrospectively or in the next billing cycle, depending on user choice. Plan downgrades and cancellations are effective after the last day of the current billing period. For full details go to hpinstantink.com/terms.

Technical specifications disclaimers

- 1 Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims, Exact speed varies depending on the system configuration, software application, driver, and
- ² Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- ³ Job Storage feature requires a purchase of separate USB flash drive with a minimum of 16 GB capacity.
- ⁴ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.
- ⁵ Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh).
- ⁶ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel.
- 7 For yield information on the cartridge included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.















