

| |
|-------------------------------|
| Part No |
| Model Name |
| |
| EAN Code |
| UPC Code |
| |
| Operating System |
| LCD cover-material |
| LCD cover-color |
| Top case-material |
| Top case-color |
| Bottom case-material |
| Bottom case-color |
| Military grade |
| Panel Size |
| Backlit |
| OLED |
| Brightness |
| Resolution |
| Glare |
| Color gamut |
| Touch Panel |
| Screen-to-body ratio |
| Pantone |
| IPS-level |
| Processor |
| Chipset |
| Discrete/Share |
| Integrated GPU |
| VRAM |
| Expansion Slot(includes used) |
| |
| Total System Memory |
| On board memory |
| DIMM Memory |
| Storage |
| |
| Front-facing camera |
| Wireless |
| 3G/4G |
| NumberPad |
| ScreenPad™ |

| |
|---------------------------------|
| FingerPrint |
| Keyboard type |
| I/O ports |
| Audio |
| Voice control |
| Battery |
| Replaceable Battery |
| AC Adapter |
| Dimension (WxHxD) |
| Weight (with Battery) |
| Weight (w/o Battery) |
| Security |
| MyASUS feature |
| Built-in Apps |
| Included in the Box |
| Reparability Index (for France) |
| CSID |



90NX0441-M00S80
B1500CEAE-BQ2868

4711081541189
195553541183

Endless
Aluminum
Star Black
Plastic
Star Black
Plastic
Black
US MIL-STD 810H military-grade standard
15.6-inch
LED Backlit
LCD
250nits
FHD (1920 x 1080) 16:9
Anti-glare display
NTSC: 45%
N/A
90 %
N/A
Wide view
Intel® Core™ i7-1165G7 Processor 2.8 GHz (12M Cache, up to 4.7 GHz, 4 cores)
N/A
Share
Intel Iris X^e Graphics (available Intel® Core™ i5/i7 with dual channel memory)
N/A
1x DDR4 SO-DIMM slot
1x M.2 2280 PCIe 3.0x2
1x STD 2.5" SATA HDD
8G DDR4 on board + 8GB DDR4 SO-DIMM
8G DDR4 on board
8GB DDR4 SO-DIMM
512GB M.2 NVMe™ PCIe® 3.0 SSD
HDD Housing for storage expansion
N/A
720p HD camera//With privacy shutter
Wi-Fi 6(802.11ax)+BT5.2 (Dual band) 2*2
N/A
N/A
N/A

FingerPrint

Backlit Chiclet Keyboard with Num-key

1x HDMI 1.4

1x VGA Port (D-Sub)

1x 3.5mm Combo Audio Jack

1x RJ45 Gigabit Ethernet

1x DC-in//1x USB 2.0 Type-A

1x USB 3.2 Gen 1 Type-C support display / power delivery

2x USB 3.2 Gen 2 Type-A//Micro SD card reader

Built-in speaker

Built-in array microphone//N/A

with Cortana support

42WHrs, 3S1P, 3-cell Li-ion

No

ø4.5, 65W AC Adapter, Output: 19V DC, 3.42A, 65W, Input: 100~240V AC 50/60Hz universal

35.80 x 23.65 x 1.94 ~ 1.94 cm

1.73 kg

1.55 kg

BIOS Booting User Password Protection

Computrace ready from BIOS

HDD User Password Protection and Security

Trusted Platform Module (TPM) 2.0

Fingerprint sensor integrated with Power Key

Kensington Security Slot™

System diagnosis

Battery health charging

Fan Profile

Splendid

Tru2Life

Function key lock

WiFi SmartConnect

AppDeals

Link to MyASUS

MyASUS

N/A

6.6

1Y ON-SITE NBD